

Cisco 110 Series Unmanaged Switches Data Sheet

Updated: September 3, 2020

[Bias-Free Language](#)

Affordable, Easy-to-Use Switches for Small Business Networks, with Zero Configuration Required

Highlights

Affordable 10/100/1000-Mbps speeds for even the most bandwidth-hungry applications

5- to 24-port models that are desktop or rack mountable

Power over Ethernet models to provide power to IP phones, access points, and other devices

Works right out of the box: plug and play and no setup

Product overview

Give your office network a boost of speed and performance at a low price that takes almost no time to set up. Easily build a highly reliable network to connect your computers, printers, copiers, and other office equipment. If your business is like most small companies, you do not have an IT staff to set up your network for you. Now you can have a high-performance, business-class office network that just works, right out of the box, with the Cisco[®] 110 Series Unmanaged Switches. Users, workgroups, labs, departments, or growing offices can now deliver large amounts of multimedia, image, and video information across the network in almost no time.

Cisco 110 Series Unmanaged Switches deliver basic network connectivity and reliability for small businesses that is easy on the budget and without all the complexity. These switches provide all of the features, expandability, and investment protection you expect from Cisco, with no installation software and nothing to configure. Just plug it in, connect your computers and other business equipment, and get to work.

Cisco 110 Series Unmanaged Switches (Figure 1), part of the Cisco Small Business networking solutions, are a line of unmanaged switches that provide wire-speed Fast Ethernet and Gigabit Ethernet connectivity to connect your small business office. Available in desktop and rack-mount models, these switches are designed to suit any office space with basic network needs and to optimize power efficiency. They use less power and provide the robust, reliable connectivity your business demands, as well as support for advanced features such as Quality of Service (QoS), loop detection,

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >



affordable network solution, Cisco 110 Series switches bring the proven reliability and investment protection of Cisco networking solutions to your small business.



Figure 1.

Cisco 110 Series Unmanaged Switches

Features

Cisco 110 Series switches provide an easy-to-use solution for your small business network. They offer:

Ease of use: Cisco 110 Series switches work right out of the box, with no software to install and nothing to configure. Each switch port independently sets itself for the optimal speed and determines whether to run in half- or full-duplex mode automatically. As a standards-based Cisco solution, Cisco 110 Series switches are also designed to immediately accommodate all of the devices in your network, including:

- Support for 10 Megabits per second (Mbps), 100 Mbps, and up to 1 gigabit per second (1000 Mbps) devices in the same network
- Automatic cable detection, so you do not have to worry about using the wrong cable type
- Compatibility with network devices from other vendors

Simple setup: Designed for small office spaces, Cisco 110 Series switches are available in both compact desktop and rack-mount models. The desktop models offer a wall-mount option for discreet mounting under a desk or on the wall of an office or conference room.

High performance: Cisco 110 Series switches deliver the performance you need to run your business applications, including bandwidth-intensive video services, and avoid slow and sluggish networks. They support Gigabit Ethernet speeds, unlocking a new level of capacity and performance in your business network and letting you transfer large files in seconds.

Reduced energy costs: Cisco 110 Series switches are designed to help conserve energy by optimizing power use without compromising performance, which protects our environment and reduces your energy costs. In addition, they support the Energy Efficient Ethernet (IEEE 802.3az)

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >

link and putting the link into a sleep state during quiet periods. Most of the switches have no fans, so they run silently and unobtrusively while lowering energy costs.

Power over Ethernet (PoE): Cisco 110 Series switches are available with PoE ports on both Fast Ethernet and Gigabit Ethernet models. This capability simplifies the deployment of IP telephony, wireless, video surveillance, and other solutions by allowing you to connect and power network endpoints over a single Ethernet cable. With no need to install separate power supplies for IP phones or wireless access points, you can take advantage of advanced communications technologies more quickly and at a lower cost.

Support for advanced technologies: All switches include advanced Cisco traffic-handling features to keep your applications running at peak performance. Integrated QoS intelligence on all models automatically prioritizes delay-sensitive services such as voice or video to improve your network's performance. Loop detection helps discover loops in the network that you might have accidentally created, thus avoiding broadcast storms that will bring your network to a stall. Cable diagnostics help to quickly identify and troubleshoot network cabling faults and issues. Fast store-and-forward switching identifies damaged packets and prevents them from being passed on through the network. All of these features run automatically, with no management or configuration required.

Peace of mind: Cisco 110 Series switches deliver the rock-solid reliability you expect from a Cisco switch. The solution has been rigorously tested to make sure of optimal uptime and performance. In addition, the limited lifetime hardware warranty provides peace of mind.

Specifications

Table 1 lists the specifications, package contents, and minimum requirements for the Cisco 110 Series.

Table 1. Specifications for Cisco 110 Series Switches

Specifications	Description
Standards	IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, IEEE 802.3z Gigabit Ethernet, IEEE 802.3x Flow Control, 802.1p priority, Energy Efficient Ethernet, 802.3af, Power over Ethernet
Cabling type	Category 5e or better
LED indicators	System/PWR, link/activity, 100M, * PoE, * Max PoE, cable diagnostics, loop detection, gigabit, * mini-GBIC* *if present
Physical Interfaces	
Ports	10/100/1000 Ethernet, with support for 802.3af PoE, power port for AC adapter or power cord
Power supply	SF110D-05, SF110D-08: DC 12V, 500mA SF110D-16, SG110D-08, SG110D-05: DC 12V, 1.0A SF110D-08HP, SG110D-8HP: DC 48V. 1.25A SF110-16, SF110D-16HP, SF110-24, SF112-24, SG110-16, SG110-16HP, SG110-24, SG110-24HP, SG112-24: 110-240VAC, 50-60 Hz, internal, universal
Lock slot	Slot for Kensington lock
Physical Specifications	
Physical dimensions (W x D x H)	SF110D-05: 4.33 x 2.95 x 1.18 inches (110 x 75 x 30 mm) SF110D-08: 6.30 x 3.54 x 1.18 inches (160 x 90 x 30 mm) SF110D-08HP: 6.30 x 5.06 x 1.18 inches (160 x 129 x 30 mm) SF110D-16: 6.30 x 3.54 x 1.73 inches (160 x 90 x 44 mm) SF110-16: 11 x 6.69 x 1.73 inches (279 x 170 x 44 mm)

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >

Specifications	Description
	<p>SF110-24: 11 x 6.69 x 1.73 inches (279 x 170 x 44 mm)</p> <p>SF112-24: 17.32 x 7.97 x 1.73 inches (440 x 203 x 44 mm)</p> <p>SG110D-05: 4.33 x 2.95 x 1.18 inches (110 x 75 x 30 mm)</p> <p>SG110D-08: 6.30 x 4.07 x 1.18 inches (160 x 104 x 30 mm)</p> <p>SG110D-08HP: 6.30 x 5.06 x 1.18 inches (160 x 129 x 30 mm)</p> <p>SG110-16: 11 x 6.7 x 1.73 inches (279 x 170 x 44 mm)</p> <p>SG110-16HP: 11 x 6.7 x 1.73 inches (279 x 170 x 44 mm)</p> <p>SG110-24: 17.32 x 7.97 x 1.73 inches (440 x 203 x 44 mm)</p> <p>SG110-24HP: 17.32 x 7.97 x 1.73 inches (440 x 203 x 44 mm)</p> <p>SG112-24: 11 x 6.7 x 1.73 inches (279.4 x 170 x 44 mm)</p>
Weight	<p>SF110D-05: 1.01 lb. (0.46 kg)</p> <p>SF110D-08: 1.39 lb. (0.63 kg)</p> <p>SF110D-08HP: 1.08 lb. (0.49 kg)</p> <p>SF110D-16: 0.99 lb. (0.45 kg)</p> <p>SF110-16: 2.54 lb. (1.15 kg)</p> <p>SF110D-16HP: 3.00 lb. (1.36 kg)</p> <p>SF110-24: 2.14 lb. (0.97 kg)</p> <p>SF112-24: 4.25 lb. (1.93 kg)</p> <p>SG110D-05: 0.51 lb. (0.23 kg)</p> <p>SG110D-08: 0.95 lb. (0.43 kg)</p> <p>SG110D-08HP: 1.12 lb. (0.51 kg)</p> <p>SG110-16: 2.14 lb. (0.97 kg)</p> <p>SG110-16HP: 2.87 lb. (1.30 kg)</p> <p>SG110-24: 5.80 lb. (2.63 kg)</p> <p>SG110-24HP: 6.57 lb. (2.98 kg)</p> <p>SG112-24: 3.42 lb. (1.55 kg)</p>
Ports	<p>SF110D-05: 5 RJ-45 connectors for 10BASE-T/100BASE-TX</p> <p>SF110D-08: 8 RJ-45 connectors for 10BASE-T/100BASE-TX</p> <p>SF110D-08HP: 8 RJ-45 connectors for 10BASE-T/100BASE-TX;</p> <p>SF110D-16: 16 RJ-45 connectors for 10BASE-T/100BASE-TX</p> <p>SF110D-16HP: 16 RJ-45 connectors for 10BASE-T/100BASE-TX</p> <p>SF112-24: 16 RJ-45 connectors for 10BASE-T/100BASE-TX</p>

Specifications	Description		
	<p>SF110-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX</p> <p>SF112-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX; with 2 combo mini-GBIC slots</p> <p>SG110D-08: 8 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports</p> <p>SG110D-08HP: 8 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports</p> <p>SG110-16: 16 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports</p> <p>SG110-16HP: 16 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports</p> <p>SG110-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports with 2 combo mini-GBIC slots</p> <p>SG110-24HP: 24 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports with 2 combo mini-GBIC slots</p> <p>SG112-24: 24 RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T ports with 2 combo mini-GBIC slots</p> <p>All units: automatic Medium Dependent Interface (MDI) and MDI crossover (MDI-X); autonegotiated port for connecting 10-, 100-, 1000-Mbps devices</p>		
Power over Ethernet (PoE)	Model Name SF110D-08HP SF110D-16HP SG110D-08HP SG110-16HP SG110-24HP	Power Dedicated to PoE 32 watts 64 watts 32 watts 64 watts 100 watts	Number of PoE Ports 4 8 4 8 12
Fan/fanless models	All models have no fans and are fanless, except for SG100-24HP		
Performance			

Specifications	Description
Switching capacity	SF110D-05: 1 Gbps SF110D-08: 1.6 Gbps SF110D-08HP: 1.6 Gbps SF110D-16: 3.2 Gbps SF110-16: 3.2 Gbps SF110D-16HP: 3.2 Gbps SF110-24: 4.8 Gbps SF112-24: 8.8 Gbps SG110D-05: 10 Gbps SG110D-08: 16 Gbps SG110D-08HP: 16 Gbps SG110-16: 32 Gbps SG110-16HP: 32 Gbps SG110-24: 48 Gbps SG110-24HP: 48 Gbps SG112-24: 48 Gbps
Forwarding capacity	Forwarding rate in million packets per second (mpps) (based on 64-byte

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) >
 [Change Settings](#) >

Specifications	Description
	packets): SF110D-05: 0.74 mpps SF110D-08: 1.4. mpps S110D-08HP: 1.2 mpps SF110D-16: 1.4 mpps SF110-16: 1.4 mpps SF110D-16HP: 1.4 mpps SF110-24: 3.6 mpps SF112-24: 6.5 mpps SG110D-05: 7.4 mpps SG110D-08: 11.9 mpps SG110D-08HP: 11.9 mpps SG110-16: 23.8 mpps SG110-16HP: 23.8 mpps SG110-24: 35.7 mpps SG110-24HP: 35.7 mpps SG112-24: 35.7 mpps
Capabilities	
Head-of-line (HOL) blocking	HOL blocking prevention
Jumbo frame	9216 bytes
Quality of service (QoS)	802.1p priority based, 4 hardware queues, priority queuing and Weighted Round-Robin (WRR)
Loop detection	Helps discover loops in the network to avoid broadcast storms
Cable diagnostics	Quickly identify and troubleshoot network cable faults and/or shorts

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >

Specifications	Description
Mounting and Physical Security	
Mounting options	Desktop or rack mount
Physical security lock	Kensington lock slot
Environmental	
Compliance/certifications	UL (UL 60950), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A, FCC Class B* *select models
Operating temperature	32° to 104°F (0° to 40°C)
Storage temperature	-4° to 158°F (-20° to 70°C)
Operating humidity	10% to 90%, relative, noncondensing
Storage humidity	5% to 90%, relative, noncondensing
Package Contents	
<ul style="list-style-type: none"> • Cisco 110 Series switch • Power cord/power adapter 	

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >

Specifications	Description
	<ul style="list-style-type: none"> • Mounting hardware
Minimum Requirements	
	<ul style="list-style-type: none"> • Devices supporting 802.3 Ethernet, 802.u Faster Ethernet, or 802.3ab Gigabit Ethernet • Cat5 or better Ethernet cable • Network interface card for each computer
Warranty	
Cisco 110 Series switch	Limited lifetime

Ordering information

Table 2 gives ordering information for the Cisco 110 Series Unmanaged Switches.

Table 2. Ordering information for Cisco 110 Series Unmanaged Switches

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >

Part Number	Description
SF110D-05-xx	Cisco SF110D-05 - 5-Port 10/100 Desktop Switch
SF110D-08-xx	Cisco SF110D-08 8-port 10/100 Desktop Switch
SF110D-08HP-xx	Cisco SF110D-08P 8-port 10/100 PoE Desktop Switch
SF110D-16-xx	Cisco SF110D-16 16-port 10/100 Desktop Switch
SF110D-16HP-xx	Cisco SF110D-16P 16-port 10/100 PoE Desktop Switch
SF110-16-xx	Cisco SF110-16 16-Port 10/100 Switch
SF110-24-xx	Cisco SF110-24 24-Port 10/100 Switch
SF112-24-xx	Cisco SF112-24 24-port 10/100 + 2 Mini-GBIC & 2 GE Uplink
SG110D-05-xx	Cisco SG110D-05 5-port Gigabit Desktop Switch
SG110D-08-xx	Cisco SG110D-08 8-Port Gigabit Switch
SG110D-08HP-xx	Cisco SG110D-08P 8-Port Gigabit PoE Switch
SG110-16-xx	Cisco SG110-16 16-Port Gigabit Switch
SG110-16HP-xx	Cisco SG110-16HP 16-Port PoE Gigabit Switch
SG112-24-xx	Cisco SG112-24 COMPACT 24-port Gig Switch-2 Mini-GBIC Ports
SG110-24-xx	Cisco SG110-24 24-port Gigabit Switch + 2 Mini GBIC Ports 1U

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >

Part Number	Description
SG110-24HP-xx	Cisco SG110-24HP 24-Port PoE Gigabit Switch

The -xx in the Product Order ID Number is a country-/region-specific suffix. For example, the complete Product Order ID Number for SG110D-08 for the United States is SG110D-08-NA. Please refer to Table 3 for the correct suffix to use for your country/region.

Table 3. Country/region suffix for product order ID number

Suffix	Country/region
-NA	USA, Canada, Mexico, Colombia, Chile, and rest of Latin America
-BR	Brazil
-AR	Argentina
-EU	European Economic Area, Switzerland, Turkey, Russia, Ukraine, Israel, United Arab Emirates, Egypt, South Africa
-UK	United Kingdom, Saudi Arabia, Qatar, Kuwait
-AU	Australia, New Zealand
-JP	Japan

The products may also be available in countries or regions not listed above. Not all product models are offered in all countries/regions. Please consult with your local Cisco sales representative or Cisco partner for more details.

Cisco limited lifetime warranty for Cisco Small Business products

This Cisco Small Business product comes with a limited lifetime hardware warranty. Product warranty terms and other information applicable to Cisco products are available at <https://www.cisco.com/go/warranty>.

Services for Small Business

Reduce downtime with fast, expert technical support and flexible hardware coverage. Cisco Services improve network availability and help you get the most value from your Cisco products. Service plans for your Cisco Small Business products provide more support than a product warranty. A warranty protects you against product defects, and a majority of support calls are unrelated to faulty materials or

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >

manufacturing. Most callers ask about product features, technical problems, or how to expand their network.

Cisco offers an unlimited number of calls and no restrictions on call duration, so you can get the help you need and the most from your Cisco product.

For more information about Cisco Services, see <https://www.cisco.com/go/sbs>.

Cisco environmental sustainability

Information about Cisco’s environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the “Environment Sustainability” section of Cisco’s Corporate Social Responsibility (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the “Environment Sustainability” section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	Materials
Information on electronic waste laws and regulations, including products, batteries, and packaging	WEEE compliance

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more.](#)

For more information

For more information about Cisco Small Business products and solutions,

By continuing to use our website, you acknowledge the use of cookies.

[Privacy Statement](#) > [Change Settings](#) >

Quick Links —

[About Cisco](#)

[Contact Us](#)

[Careers](#)

[Connect with a partner](#)

Resources and Legal —

[Feedback](#)

[Help](#)

[Terms & Conditions](#)

[Privacy](#)

[Cookies / Do not sell or share my personal data](#)

[Accessibility](#)

[Trademarks](#)

[Supply Chain Transparency](#)

[Newsroom](#)

[Sitemap](#)

